Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1. (cancelled)
- 2. (cancelled)
- 3. (currently amended) The scanning module of claim $\frac{1}{2}$, $\frac{8}{2}$ wherein the radiographic sheet is a phosphorous sheet.
- 4. (currently amended) The scanning module of claim 1, 8 wherein the laser is a multimode, 635 nanometer, 100 mW, or a single mode 635 nanometer, 100 mW laser.
- 5. (currently amended) The scanning module of claim $\frac{1}{2}$, wherein the filter is a blue filter.
- 6. (currently amended) The scanning module of claim $\frac{1}{2}$, $\frac{8}{2}$ wherein the housing comprises a plastic, a polycarbonate, a composite, or a metal.
- 7. (currently amended) The scanning module of claim $\frac{1}{2}$, wherein the housing is a molded one-piece construction.
- 8. (currently amended) The seanning module of claim 1, A scanning module for emitting light to and collecting light from a photo-stimulable radiographic sheet, comprising:
- (a) a housing comprising a channel; a cylindrical center chamber in communication with the channel comprising a mirrored surface; a first opening communicating with the cylindrical chamber; and a second opening communicating with the cylindrical chamber;

- (b) a laser disposed in the housing and adapted to generate a beam of stimulating electromagnetic radiation through the channel and the first opening onto a stimulated area of the photo-stimulatable radiographic sheet, and wherein the stimulated area emits light and reflected light, both of which enter the first opening and the cylindrical chamber;
- (c) a light detector disposed in the second opening for receiving light emitted and reflected into the cylindrical chamber;
- (d) a filter disposed at the second opening of the housing for selectively passing only the emitted light from the stimulated area of the photo-stimulatable radiographic sheet to the light detector; and

wherein the center chamber is an elliptical reflector comprising an overall length between 15 mm and 30 mm and a degree of curvature in the chamber between 20 degrees and 30 degrees.

- 9. (currently amended) The scanning module of claim $\frac{1}{2}$, wherein the optical filter comprises an anti-reflective coating.
 - 10. (cancelled)
 - 11. (cancelled)
 - 12. (cancelled)
- 13. (currently amended) The scanning system of claim 10, 19 wherein the radiographic sheet is a phosphorous sheet.
- 14. (currently amended) The scanning system of claim 10, 19 wherein the laser is a multimode, 635 nanometer, 100 mW, or a single mode 635 nanometer, 100 mW laser.
- 15. (currently amended) The scanning system of claim 10, 19 wherein the filter is a blue filter is disposed at the second opening.
 - 16. (cancelled)

- 17. (currently amended) The scanning system of claim 10, 19 wherein the housing comprises a plastic, a polycarbonate, a composite or a metal.
- 18. (currently amended) The scanning system of claim 10, 19 wherein the housing is of a molded one piece construction.
- 19. (currently amended) The seanning system of claim 10, A system for emitting light to and collecting light from a photo-stimulatable radiographic sheet comprising:
- (a) a housing comprising a channel; a cylindrical center chamber in communication with the channel comprising a mirrored surface; a first opening communicating with the cylindrical chamber; and a second opening communicating with the cylindrical chamber;
- (b) an analog to digital converter adapted to receive a signal from the light detector;
- (c) a control processing unit adapted to receive the signal from the analog to digital converter, wherein the control processing unit stores the signal;
- (d) an output device adapted to receive the signal from the control processing unit; and

wherein the center chamber is an elliptical reflector having an overall length between 15 and 30 mm and a degree of curvature in the chamber between 20 and 30 degrees.

20. (currently amended) The scanning system of claim 10, 19 wherein the multiple modules systems are mounted on a rotating disc to scan radiographic media mounted on an internal rotating drum.